Printing date 02/01/2023

Reviewed on 02/01/2023

### **1** Identification

- · Product identifier
- Trade name: <u>LiteFix liquid</u>
- Article number: 1259-L
- · Application of the substance / the mixture Laboratory chemicals

· Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Electron Microscopy Sciences 1560 Industry Road USA-Hatfield, PA 19440 Tel: 215-412-8400 Fax: 215-412-8450 email: sgkcck@aol.com www.emsdiasum.com

• Information department: Product safety department • Emergency telephone number: ChemTrec 1-800-424-9300 Contract CCN7661

1-703-527-3887

# 2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



Skin Irritation 2 Sensitization - Skin 1 H315 Causes skin irritation. H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

#### · Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

Hazard-determining components of labeling: Methyl Methacrylate tetramethylene dimethacrylate
Hazard statements Highly flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation.

 $(Contd. \ on \ page \ 2)$ 

<sup>–</sup> ÚS

Printing date 02/01/2023

Reviewed on 02/01/2023

# Trade name: LiteFix liquid

2082-81-7 tetramethylene dimethacrylate

	(Contd. of page 1)
· Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Contaminated work clothing must not be allowed out of the workplace.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
Call a poison center/doctor if you feel unwell.	
Specific treatment (see on this label).	
Take off contaminated clothing and wash it before reuse.	
If skin irritation or rash occurs: Get medical advice/attention.	
Wash contaminated clothing before reuse.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulations	).
· Classification system: · NFPA ratings (scale 0 - 4)	
· IVI I A railings (scale 0 - 4)	
Health = 1	
Fire = $3$	
$\frac{1}{1} \frac{0}{1} \frac{1}{1} \frac{1}$	
· HMIS-ratings (scale 0 - 4)	
$\frac{\text{HEALTH}}{1} Health = 1$	
FIRE 3 $Fire = 3$	
<b>REACTIVITY</b> $O$ Reactivity = 0	
· Other hazards	
· Results of PBT and vPvB assessment	
• <b><i>PBT</i></b> : Not applicable.	
• <b>vPvB:</b> Not applicable.	
3 Composition/information on ingredients	
· Chemical characterization: Mixtures	
• Description: Mixture of the substances listed below with nonhazardous additions.	
· Dangerous components:	
80-62-6 Methyl Methacrylate	>50- <i>≤</i> 100%

(Contd. on page 3)

>2.5-*≤*10%

US

*Printing date 02/01/2023* 

Reviewed on 02/01/2023

Trade name: LiteFix liquid

(Contd. of page 2)

### 4 First-aid measures

### · Description of first aid measures

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

### **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

### **6** Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- $\cdot$  Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

- · Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.
- See Section 8 for information on personal protection equips See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

• PAC-1:
 80-62-6 Methyl Methacrylate
 • PAC-2:

80-62-6 Methyl Methacrylate

· PAC-3:

80-62-6 Methyl Methacrylate

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

17 ppm

120 ppm

570 ppm

US

Printing date 02/01/2023

Reviewed on 02/01/2023

#### Trade name: LiteFix liquid

(Contd. of page 3)

Prevent formation of aerosols.
Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

#### · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

#### 80-62-6 Methyl Methacrylate

PEL Long-term value: 410 mg/m<sup>3</sup>, 100 ppm

REL Long-term value: 410 mg/m<sup>3</sup>, 100 ppm

TLV Short-term value: 100 ppm Long-term value: 50 ppm DSEN, A4

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (Contd. on page 5)

id. on page 5)

Printing date 02/01/2023

Reviewed on 02/01/2023

#### Trade name: LiteFix liquid

#### · Material of gloves

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

# $\cdot$ Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### • Eye protection:



Tightly sealed goggles

# 9 Physical and chemical properties

General Information Appearance:	
Form:	Liquid
Color:	Colorless
Odor:	Ester-like
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	101 °C (213.8 °F)
Flash point:	10 °C (50 °F)
Flammability (solid, gaseous):	Highly flammable.
Ignition temperature:	430 °C (806 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	2.1 Vol %
Upper:	12.5 Vol %
Vapor pressure at 20 °C (68 °F):	47 hPa (35.3 mm Hg)
Density at 20 °C (68 °F):	0.945 g/cm <sup>3</sup> (7.88603 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	m). Not determined

Printing date 02/01/2023

Reviewed on 02/01/2023

Trade name: LiteFix liquid

	(Contd. of )	page :
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
VOC content:	0.00~%	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

### **10 Stability and reactivity**

• *Reactivity* No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### **11** Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:
- The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

- · IARC (International Agency for Research on Cancer)
- 80-62-6 *Methyl Methacrylate*

#### · NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety Health Administration)

None of the ingredients is listed.

# **12** Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 7)

3

(Contd. of page 6)

# Safety Data Sheet acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

Trade name: LiteFix liquid

· Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

• Results of PBT and vPvB assessment

• *PBT:* Not applicable.

• **vPvB:** Not applicable.

 $\cdot$  Other adverse effects No further relevant information available.

# **13 Disposal considerations**

• Waste treatment methods • Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

· UN-Number · DOT, ADR, IMDG, IATA	UN1247
· UN proper shipping name	
·DOT	Methyl methacrylate monomer, stabilized mixture
· ADR	1247 METHYL METHACRYLATE MONOMER, STABILIZE
· IMDG, IATA	mixture METHYL METHACRYLATE MONOMER, STABILIZED mixture
· Transport hazard class(es)	
·DOT	
P RANGE CON	
· Class	3 Flammable liquids
· Label	3
ADR, IMDG, IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards:	Not applicable.
· Special precautions for user · Hazard identification number (Kemlo	Warning: Flammable liquids

Printing date 02/01/2023

Reviewed on 02/01/2023

Trade name: LiteFix liquid

	(Contd. of page
· EMS Number:	F-E,S-D
· Stowage Category	С
· Stowage Code	SW1 Protected from sources of heat.
	SW2 Clear of living quarters.
· Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
·DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
· ADR	
· Excepted quantities (EQ)	Code: E2
• • • • •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· IMDG	
· Limited quantities (LQ)	1L
Excepted quantities $(EQ)$	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZE
	MIXTURE, 3, II

# **15 Regulatory information**

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

• Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

80-62-6 Methyl Methacrylate

• TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

80-62-6 Methyl Methacrylate

· Proposition 65

• Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 9)

<sup>-</sup> US

Printing date 02/01/2023

Reviewed on 02/01/2023

Trade name: LiteFix liquid

(Contd. of page 8)

E, NL

A4

· Carcinogenic c	categories
------------------	------------

 $\cdot$  EPA (Environmental Protection Agency)

80-62-6 Methyl Methacrylate
• TLV (Threshold Limit Value)

80-62-6 Methyl Methacrylate

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

· Hazard-determining components of labeling: Methyl Methacrylate tetramethylene dimethacrylate · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 10)

Printing date 02/01/2023

Reviewed on 02/01/2023

#### Trade name: LiteFix liquid

(Contd. of page 9)

### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Contact:

· Date of preparation / last revision 02/01/2023 • Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Skin Irritation 2: Skin corrosion/irritation - Category 2 Sensitization - Skin 1: Skin sensitisation - Category 1 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3