

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/12/2023

Reviewed on 01/12/2023

1 Identification

- **Product identifier**
- **Trade name:** GRAPHITE SPRAY ADHESIVE
- **Article number:** 12648
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Electron Microscopy Sciences
1560 Industry Road
USA-Hatfield, PA 19440
Tel: 215-412-8400 Fax: 215-412-8450
email: sgkcck@aol.com
www.emsdiasum.com
- **Information department:** Product safety department
- **Emergency telephone number:**
ChemTrec 1-800-424-9300 Contract CCN7661
1-703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Aspiration Hazard 1

H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

Sensitization - Skin 1

H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

heptane

propan-2-ol

methylcyclohexane

octane

- **Hazard statements**

Causes skin irritation.

Causes serious eye irritation.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/12/2023

Reviewed on 01/12/2023

Trade name: GRAPHITE SPRAY ADHESIVE

(Contd. of page 1)

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

· **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves / eye protection / face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Call a poison center/doctor if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 4

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 2

Fire = 4

Reactivity = 1

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

| | | |
|----------|-------------------|-----------|
| 142-82-5 | heptane | >25-≤50% |
| 67-63-0 | propan-2-ol | >10-≤25% |
| 74-98-6 | propane | >10-≤25% |
| 106-97-8 | butane, pure | >2.5-≤10% |
| 108-87-2 | methylcyclohexane | >2.5-≤10% |

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/12/2023

Reviewed on 01/12/2023

Trade name: GRAPHITE SPRAY ADHESIVE

(Contd. of page 2)

| | | |
|-----------|----------|-----------|
| 111-65-9 | octane | >2.5-≤10% |
| 7782-42-5 | Graphite | >2.5-≤10% |

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **Special hazards arising from the substance or mixture** No further relevant information available.

- **Advice for firefighters**

- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.

- **Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- **PAC-1:**

| | | |
|----------|--------------|-----------|
| 142-82-5 | heptane | 500 ppm |
| 67-63-0 | propan-2-ol | 400 ppm |
| 74-98-6 | propane | 5500* ppm |
| 106-97-8 | butane, pure | 5500* ppm |

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/12/2023

Reviewed on 01/12/2023

Trade name: GRAPHITE SPRAY ADHESIVE

(Contd. of page 3)

| | | |
|-----------------|-------------------|--------------|
| 108-87-2 | methylcyclohexane | 1200* ppm |
| 111-65-9 | octane | 230 ppm |
| · PAC-2: | | |
| 142-82-5 | heptane | 830 ppm |
| 67-63-0 | propan-2-ol | 2000* ppm |
| 74-98-6 | propane | 17000** ppm |
| 106-97-8 | butane, pure | 17000** ppm |
| 108-87-2 | methylcyclohexane | 1700* ppm |
| 111-65-9 | octane | 385 ppm |
| · PAC-3: | | |
| 142-82-5 | heptane | 5000* ppm |
| 67-63-0 | propan-2-ol | 12000** ppm |
| 74-98-6 | propane | 33000*** ppm |
| 106-97-8 | butane, pure | 53000*** ppm |
| 108-87-2 | methylcyclohexane | 10000** ppm |
| 111-65-9 | octane | 5000** ppm |

7 Handling and storage

- **Handling:**

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

- **Information about protection against explosions and fires:**

Protect from heat.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurized containers.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:**

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Control parameters**

- **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/12/2023

Reviewed on 01/12/2023

Trade name: GRAPHITE SPRAY ADHESIVE

(Contd. of page 4)

142-82-5 heptane

| | |
|-----|---|
| PEL | Long-term value: 2000 mg/m ³ , 500 ppm |
| REL | Long-term value: 350 mg/m ³ , 85 ppm Ceiling limit value: 1800* mg/m ³ , 440* ppm *15-min |
| TLV | Short-term value: 500 ppm Long-term value: 400 ppm |

67-63-0 propan-2-ol

| | |
|-----|--|
| PEL | Long-term value: 980 mg/m ³ , 400 ppm |
| REL | Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm |
| TLV | Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4 |

74-98-6 propane

| | |
|-----|--|
| PEL | Long-term value: 1800 mg/m ³ , 1000 ppm |
| REL | Long-term value: 1800 mg/m ³ , 1000 ppm |
| TLV | see Appendix F Minimal oxygen content (D, EX) |

106-97-8 butane, pure

| | |
|-----|---|
| REL | Long-term value: 1900 mg/m ³ , 800 ppm |
| TLV | Short-term value: 1000 ppm (EX) |

108-87-2 methylcyclohexane

| | |
|-----|---|
| PEL | Long-term value: 2000 mg/m ³ , 500 ppm |
| REL | Long-term value: 1600 mg/m ³ , 400 ppm |
| TLV | Long-term value: 400 ppm |

111-65-9 octane

| | |
|-----|---|
| PEL | Long-term value: 2350 mg/m ³ , 500 ppm n-Octane only |
| REL | Long-term value: 350 mg/m ³ , 75 ppm Ceiling limit value: 1800* mg/m ³ , 385* ppm *15 min |
| TLV | Long-term value: 300 ppm |

· Ingredients with biological limit values:**67-63-0 propan-2-ol**

| | |
|-----|---|
| BEI | 40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific) |
|-----|---|

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/12/2023

Reviewed on 01/12/2023

Trade name: GRAPHITE SPRAY ADHESIVE

(Contd. of page 5)

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

| | |
|------------------------|-----------------|
| Form: | Aerosol |
| Color: | Black |
| Odor: | Characteristic |
| Odor threshold: | Not determined. |

· **pH-value:** Not determined.

· **Change in condition**

| | |
|-------------------------------------|----------------------|
| Melting point/Melting range: | <-91 °C (<-131.8 °F) |
| Boiling point/Boiling range: | 98 °C (208.4 °F) |

· **Flash point:** -4 °C (24.8 °F)

· **Flammability (solid, gaseous):** Not flammable.

· **Ignition temperature:** 215 °C (419 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

| | |
|---------------|-----------|
| Lower: | 1.1 Vol % |
|---------------|-----------|

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/12/2023

Reviewed on 01/12/2023

Trade name: GRAPHITE SPRAY ADHESIVE

(Contd. of page 6)

| | |
|---|--|
| Upper: | 12 Vol % |
| · Vapor pressure at 20 °C (68 °F): | 40 hPa (30 mm Hg) |
| · Density at 20 °C (68 °F): | 0.684 g/cm ³ (5.70798 lbs/gal) |
| · Relative density | Not determined. |
| · Vapor density | Not determined. |
| · Evaporation rate | Not applicable. |
| · Solubility in / Miscibility with Water: | Fully miscible. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 95.0 % |
| VOC content: | 95.00 % |
| | 649.8 g/l / 5.42 lb/gal |
| Solids content: | 0.0 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

106-97-8 butane, pure

| | | |
|------------|----------|----------------|
| Inhalative | LC50/4 h | 658 mg/l (rat) |
|------------|----------|----------------|

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/12/2023

Reviewed on 01/12/2023

Trade name: GRAPHITE SPRAY ADHESIVE

(Contd. of page 7)

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

67-63-0 | propan-2-ol

3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Ecotoxicological effects:**

- **Remark:** Very toxic for fish

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- **UN-Number**

- **DOT, ADR, IMDG, IATA**

UNI950

- **UN proper shipping name**

- **DOT**

Aerosols, flammable

- **ADR**

1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS

- **IMDG**

AEROSOLS, MARINE POLLUTANT

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/12/2023

Reviewed on 01/12/2023

Trade name: GRAPHITE SPRAY ADHESIVE

(Contd. of page 8)

· **IATA** AEROSOLS, flammable· **Transport hazard class(es)**· **DOT**

· **Class** 2.1 Gases
 · **Label** 2.1

· **ADR**

· **Class** 2 5F Gases
 · **Label** 2.1

· **IMDG**

· **Class** 2.1 Gases
 · **Label** 2.1

· **IATA**

· **Class** 2.1 Gases
 · **Label** 2.1

· **Packing group**· **DOT, ADR, IMDG, IATA** Void

· **Environmental hazards:** Product contains environmentally hazardous substances: heptane
 · **Marine pollutant:** Symbol (fish and tree)
 · **Special marking (ADR):** Symbol (fish and tree)

· **Special precautions for user** Warning: Gases· **Hazard identification number (Kemler code):** -· **EMS Number:** F-D,S-U· **Stowage Code**

SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· **Segregation Code**

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2.

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/12/2023

Reviewed on 01/12/2023

Trade name: GRAPHITE SPRAY ADHESIVE

(Contd. of page 9)

| | |
|---|---|
| . | For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · DOT | |
| · Quantity limitations | On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg |
| · ADR | |
| · Excepted quantities (EQ) | Code: E0 Not permitted as Excepted Quantity |
| · IMDG | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E0 Not permitted as Excepted Quantity |
| · UN "Model Regulation": | UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS |

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

67-63-0 | propan-2-ol

· TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

142-82-5 | heptane

D

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/12/2023

Reviewed on 01/12/2023

Trade name: GRAPHITE SPRAY ADHESIVE

(Contd. of page 10)

· **TLV (Threshold Limit Value)**

67-63-0 | propan-2-ol

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS07 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

heptane

propan-2-ol

methylcyclohexane

octane

· **Hazard statements**

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

· **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves / eye protection / face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin: Wash with plenty of water.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Call a poison center/doctor if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/12/2023

Reviewed on 01/12/2023

Trade name: GRAPHITE SPRAY ADHESIVE

(Contd. of page 11)

· Contact:**· Date of preparation / last revision** 01/12/2023**· Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety **Health**

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Sensitization - Skin 1: Skin sensitisation – Category 1

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

Aspiration Hazard 1: Aspiration hazard – Category 1

US