

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/07/2023

Reviewed on 07/07/2023

## 1 Identification

- **Product identifier**
- **Trade name:** Carbon Conductive Adhesive 502
- **Article number:** 12694-30, 12684-30
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Electron Microscopy Sciences  
1560 Industry Road  
USA-Hatfield, PA 19440  
Tel: 215-412-8400 Fax: 215-412-8450  
email: sgkcck@aol.com  
www.emsdiasum.com
- **Information department:** Product safety department
- **Emergency telephone number:**  
ChemTrec 1-800-424-9300 Contract CCN7661  
1-703-527-3887

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer. Route of exposure:  
Inhalation.

GHS07

Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger
- **Hazard-determining components of labeling:**  
METHYL ETHYL KETONE  
Carbon black

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/07/2023

Reviewed on 07/07/2023

Trade name: Carbon Conductive Adhesive 502

(Contd. of page 1)

- **Hazard statements**

Highly flammable liquid and vapor.  
 Causes serious eye irritation.  
 Suspected of causing cancer. Route of exposure: Inhalation.  
 May cause drowsiness or dizziness.

- **Precautionary statements**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Ground/bond container and receiving equipment.  
 Use explosion-proof electrical/ventilating/lighting/equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
 Continue rinsing.  
 IF exposed or concerned: Get medical advice/attention.  
 Call a poison center/doctor if you feel unwell.  
 If eye irritation persists: Get medical advice/attention.  
 In case of fire: Use CO2, powder or water spray to extinguish.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Store in a well-ventilated place. Keep cool.  
 Store locked up.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

78-93-3	METHYL ETHYL KETONE	>50-≤100%
---------	---------------------	-----------

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/07/2023

Reviewed on 07/07/2023

**Trade name: Carbon Conductive Adhesive 502**

(Contd. of page 2)

1333-86-4	Carbon black	>2.5-≤10%
7782-42-5	Graphite	>2.5-≤10%

## 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

- **PAC-1:**

78-93-3	METHYL ETHYL KETONE	200 ppm
1333-86-4	Carbon black	9 mg/m <sup>3</sup>

- **PAC-2:**

78-93-3	METHYL ETHYL KETONE	2700* ppm
1333-86-4	Carbon black	99 mg/m <sup>3</sup>

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/07/2023

Reviewed on 07/07/2023

Trade name: Carbon Conductive Adhesive 502

(Contd. of page 3)

## · PAC-3:

78-93-3	METHYL ETHYL KETONE	4000* ppm
1333-86-4	Carbon black	590 mg/m <sup>3</sup>

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect from heat.  
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

### 78-93-3 METHYL ETHYL KETONE

PEL	Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 885 mg/m <sup>3</sup> , 300 ppm Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
TLV	Short-term value: NIC-150 (300) ppm Long-term value: NIC-75 (200) ppm BEI, NIC-Skin

### 1333-86-4 Carbon black

PEL	Long-term value: 3.5 mg/m <sup>3</sup>
REL	Long-term value: 3.5* mg/m <sup>3</sup> *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV	Long-term value: 3* mg/m <sup>3</sup> *inhalable fraction, A3

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/07/2023

Reviewed on 07/07/2023

Trade name: Carbon Conductive Adhesive 502

(Contd. of page 4)

· **Ingredients with biological limit values:**

**78-93-3 METHYL ETHYL KETONE**

BEI	2 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Methyl ethyl ketone (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Black

· **Odor:** Like ketone

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: -86.1 °C (-123 °F)

Boiling point/Boiling range: 80 °C (176 °F)

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/07/2023

Reviewed on 07/07/2023

Trade name: Carbon Conductive Adhesive 502

(Contd. of page 5)

· <b>Flash point:</b>	-5 °C (23 °F)
· <b>Flammability (solid, gaseous):</b>	Highly flammable.
· <b>Auto igniting:</b>	514 °C (957.2 °F)
· <b>Decomposition temperature:</b>	Not determined.
· <b>Ignition temperature:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	Not determined.
<b>Upper:</b>	10 Vol %
· <b>Vapor pressure at 20 °C (68 °F):</b>	70 hPa (52.5 mm Hg)
· <b>Density at 20 °C (68 °F):</b>	0.869 g/cm <sup>3</sup> (7.25181 lbs/gal)
· <b>Relative density</b>	Not determined.
· <b>Vapor density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with Water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic at 20 °C (68 °F):</b>	400-800 mPas
<b>Kinematic:</b>	Not determined.
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	80.0 %
<b>VOC content:</b>	80.00 %
	695.2 g/l / 5.80 lb/gal
<b>Solids content:</b>	10.0 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/07/2023

Reviewed on 07/07/2023

Trade name: Carbon Conductive Adhesive 502

(Contd. of page 6)

## 11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

**78-93-3 METHYL ETHYL KETONE**

Oral	LD50	3,300 mg/kg (rat)
------	------	-------------------

Dermal	LD50	5,000 mg/kg (rabbit)
--------	------	----------------------

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1333-86-4	Carbon black	2B
-----------	--------------	----

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/07/2023



Reviewed on 07/07/2023

Trade name: Carbon Conductive Adhesive 502

(Contd. of page 7)

- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

<ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT, ADR, IMDG, IATA</b></li> </ul>	<p>UN1193</p>
<ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG, IATA</b></li> </ul>	<p>Ethyl methyl ketone 1193 ETHYL METHYL KETONE (METHYL ETHYL KETONE) ETHYL METHYL KETONE (METHYL ETHYL KETONE)</p>
<ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>DOT</b></li> </ul>	<p></p>
<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	<p>3 Flammable liquids 3</p>
<ul style="list-style-type: none"> <li>· <b>ADR, IMDG, IATA</b></li> </ul>	<p></p>
<ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>	<p>3 Flammable liquids 3</p>
<ul style="list-style-type: none"> <li>· <b>Packing group</b></li> <li>· <b>DOT, ADR, IMDG, IATA</b></li> </ul>	<p>II</p>
<ul style="list-style-type: none"> <li>· <b>Environmental hazards:</b></li> </ul>	<p>Not applicable.</p>
<ul style="list-style-type: none"> <li>· <b>Special precautions for user</b></li> <li>· <b>Hazard identification number (Kemler code):</b></li> <li>· <b>EMS Number:</b></li> <li>· <b>Stowage Category</b></li> </ul>	<p>Warning: Flammable liquids 33 F-E,<u>S-E</u> B</p>
<ul style="list-style-type: none"> <li>· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b></li> </ul>	<p>Not applicable.</p>
<ul style="list-style-type: none"> <li>· <b>Transport/Additional information:</b></li> <li>· <b>DOT</b></li> <li>· <b>Quantity limitations</b></li> </ul>	<p>On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L</p>
<ul style="list-style-type: none"> <li>· <b>ADR</b></li> <li>· <b>Excepted quantities (EQ)</b></li> </ul>	<p>Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml</p>

(Contd. on page 9)

US



# Safety Data Sheet

acc. to OSHA HCS

Printing date 07/07/2023

Reviewed on 07/07/2023

Trade name: Carbon Conductive Adhesive 502

(Contd. of page 8)

- **IMDG**

- Limited quantities (LQ)
- Excepted quantities (EQ)

IL

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

- UN "Model Regulation":

UN 1193 ETHYL METHYL KETONE (METHYL ETHYL KETONE), 3, II

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture  
No further relevant information available.

- Sara

- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

- Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

- TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

- Hazardous Air Pollutants

None of the ingredients is listed.

- Proposition 65

- Chemicals known to cause cancer:

1333-86-4 Carbon black

- Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

- Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

- Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- Carcinogenic categories

- EPA (Environmental Protection Agency)

78-93-3 METHYL ETHYL KETONE

I

- TLV (Threshold Limit Value)

1333-86-4 Carbon black

A4

- NIOSH-Ca (National Institute for Occupational Safety and Health)

1333-86-4 Carbon black

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms



GHS02



GHS07



GHS08

(Contd. on page 10)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 07/07/2023

Reviewed on 07/07/2023

**Trade name: Carbon Conductive Adhesive 502**

(Contd. of page 9)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*METHYL ETHYL KETONE*

*Carbon black*

· **Hazard statements**

*Highly flammable liquid and vapor.*

*Causes serious eye irritation.*

*Suspected of causing cancer. Route of exposure: Inhalation.*

*May cause drowsiness or dizziness.*

· **Precautionary statements**

*Obtain special instructions before use.*

*Do not handle until all safety precautions have been read and understood.*

*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*

*Ground/bond container and receiving equipment.*

*Use explosion-proof electrical/ventilating/lighting/equipment.*

*Use only non-sparking tools.*

*Take precautionary measures against static discharge.*

*Avoid breathing dust/fume/gas/mist/vapors/spray*

*Wash thoroughly after handling.*

*Use only outdoors or in a well-ventilated area.*

*Wear protective gloves/protective clothing/eye protection/face protection.*

*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*IF INHALED: Remove person to fresh air and keep comfortable for breathing.*

*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.*

*Continue rinsing.*

*IF exposed or concerned: Get medical advice/attention.*

*Call a poison center/doctor if you feel unwell.*

*If eye irritation persists: Get medical advice/attention.*

*In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.*

*Store in a well-ventilated place. Keep container tightly closed.*

*Store in a well-ventilated place. Keep cool.*

*Store locked up.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Contact:**

· **Date of preparation / last revision** 07/07/2023

· **Abbreviations and acronyms:**

*ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*VOC: Volatile Organic Compounds (USA, EU)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

(Contd. on page 11)

**Safety Data Sheet**  
**acc. to OSHA HCS**

Printing date 07/07/2023

Reviewed on 07/07/2023

**Trade name: Carbon Conductive Adhesive 502**

(Contd. of page 10)

*vPvB: very Persistent and very Bioaccumulative**NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety **Health****TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**BEI: Biological Exposure Limit**Flammable Liquids 2: Flammable liquids – Category 2**Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A**Carcinogenicity 2: Carcinogenicity – Category 2**Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3*

US