

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/06/2022

Reviewed on 12/06/2022

1 Identification

- **Product identifier**
- **Trade name:** Silver Paint Thinner
- **Article number:** 12697-10
- **CAS Number:**
108-10-1
- **EC number:**
203-550-1
- **Index number:**
606-004-00-4
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Electron Microscopy Sciences
1560 Industry Road
USA-Hatfield, PA 19440
Tel: 215-412-8400 Fax: 215-412-8450
email: sgkcck@aol.com
www.emsdiasum.com
- **Information department:** Product safety department
- **Emergency telephone number:**
ChemTrec 1-800-424-9300 Contract CCN7661
1-703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer.



GHS07

Acute Toxicity - Inhalation 4

H332 Harmful if inhaled.

Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

- **Label elements**

- **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/06/2022

Reviewed on 12/06/2022

Trade name: Silver Paint Thinner

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS07 GHS08

· **Signal word** *Danger*· **Hazard-determining components of labeling:***4-methylpentan-2-one*· **Hazard statements***Highly flammable liquid and vapor.**Harmful if inhaled.**Causes serious eye irritation.**Suspected of causing cancer.**May cause respiratory irritation.*· **Precautionary statements***Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Avoid breathing dust/fume/gas/mist/vapors/spray**Wash thoroughly after handling.**Use only outdoors or in a well-ventilated area.**Wear protective gloves/protective clothing/eye protection/face protection.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF INHALED: Remove person to fresh air and keep comfortable for breathing.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**IF exposed or concerned: Get medical advice/attention.**Call a poison center/doctor if you feel unwell.**If eye irritation persists: Get medical advice/attention.**In case of fire: Use CO₂, powder or water spray to extinguish.**Store in a well-ventilated place. Keep container tightly closed.**Store in a well-ventilated place. Keep cool.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.*· **Classification system:**· **NFPA ratings (scale 0 - 4)***Health = 2**Fire = 3**Reactivity = 0*· **HMIS-ratings (scale 0 - 4)***Health = 2**Fire = 3**Reactivity = 0*

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/06/2022

Reviewed on 12/06/2022

Trade name: Silver Paint Thinner

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Substances**
- **CAS No. Description**
108-10-1 4-methylpentan-2-one
- **Identification number(s)**
- **EC number:** 203-550-1
- **Index number:** 606-004-00-4

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/06/2022

Reviewed on 12/06/2022

Trade name: Silver Paint Thinner

(Contd. of page 3)

- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

75 ppm

· PAC-2:

500 ppm

· PAC-3:

3000* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:****108-10-1 4-methylpentan-2-one**PEL Long-term value: 410 mg/m³, 100 ppmREL Short-term value: 300 mg/m³, 75 ppmLong-term value: 205 mg/m³, 50 ppm

TLV Short-term value: 75 ppm

Long-term value: 20 ppm

BEI, A3

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/06/2022

Reviewed on 12/06/2022

Trade name: Silver Paint Thinner

(Contd. of page 4)

· **Ingredients with biological limit values:**

108-10-1 4-methylpentan-2-one

| | |
|-----|--------------------|
| BEI | 1 mg/L |
| | Medium: urine |
| | Time: end of shift |
| | Parameter: MIBK |

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Colorless

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: -83.5 °C (-118.3 °F)

Boiling point/Boiling range: 114-117 °C (237.2-242.6 °F)

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/06/2022

Reviewed on 12/06/2022

Trade name: Silver Paint Thinner

(Contd. of page 5)

| | |
|---|--|
| · Flash point: | 14 °C (57.2 °F) |
| · Flammability (solid, gaseous): | Highly flammable. |
| · Ignition temperature: | 460 °C (860 °F) |
| · Decomposition temperature: | Not determined. |
| · Auto igniting: | Not determined. |
| · Danger of explosion: | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| · Explosion limits: | |
| Lower: | 1.7 Vol % |
| Upper: | 9 Vol % |
| · Vapor pressure at 20 °C (68 °F): | 8 hPa (6 mm Hg) |
| · Density at 20 °C (68 °F): | 3.45 g/cm ³ (28.79025 lbs/gal) |
| · Relative density | Not determined. |
| · Vapor density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with Water at 20 °C (68 °F): | 19 g/l |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic at 20 °C (68 °F): | 0.59 mPas |
| Kinematic: | Not determined. |
| Organic solvents: | 100.0 % |
| VOC content: | 100.00 % |
| | 3,450.0 g/l / 28.79 lb/gal |
| Solids content: | 0.0 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US
(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/06/2022

Reviewed on 12/06/2022

Trade name: Silver Paint Thinner

(Contd. of page 6)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

108-10-1 4-methylpentan-2-one

| | | |
|------------|----------|---------------------|
| Oral | LD50 | 2,080 mg/kg (rat) |
| Dermal | LD50 | 16,000 mg/kg (rab) |
| Inhalative | LC50/4 h | 8.3-16.6 mg/l (rat) |

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

2B

- **NTP (National Toxicology Program)**

Substance is not listed.

- **OSHA-Ca (Occupational Safety Health Administration)**

Substance is not listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (Assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/06/2022

Reviewed on 12/06/2022

Trade name: Silver Paint Thinner

(Contd. of page 7)

· **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· **UN-Number**· **DOT, ADR, IMDG, IATA**

UNI245

· **UN proper shipping name**· **DOT**

Methyl isobutyl ketone

· **ADR**

1245 METHYL ISOBUTYL KETONE

· **IMDG, IATA**

METHYL ISOBUTYL KETONE

· **Transport hazard class(es)**· **DOT**· **Class**

3 Flammable liquids

· **Label**

3

· **ADR, IMDG, IATA**· **Class**

3 Flammable liquids

· **Label**

3

· **Packing group**· **DOT, ADR, IMDG, IATA**

II

· **Environmental hazards:**

Not applicable.

· **Special precautions for user**

Warning: Flammable liquids

· **Hazard identification number (Kemler code):** 33· **EMS Number:**

3-07

· **Stowage Category**

B

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**· **DOT**· **Quantity limitations**

On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· **Hazardous substance:**

5000 lbs, 2270 kg

· **ADR**· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/06/2022

Reviewed on 12/06/2022

Trade name: Silver Paint Thinner

(Contd. of page 8)

- | | |
|--|---|
| <ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | <ul style="list-style-type: none"> IL Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| <ul style="list-style-type: none"> · UN "Model Regulation": | <ul style="list-style-type: none"> UN 1245 METHYL ISOBUTYL KETONE, 3, II |

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

- **Sara**

- **Section 355 (extremely hazardous substances):**

Substance is not listed.

- **Section 313 (Specific toxic chemical listings):**

Substance is listed.

- **TSCA (Toxic Substances Control Act):**

ACTIVE

- **Hazardous Air Pollutants**

Substance is listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

Substance is listed.

- **Chemicals known to cause reproductive toxicity for females:**

Substance is not listed.

- **Chemicals known to cause reproductive toxicity for males:**

Substance is not listed.

- **Chemicals known to cause developmental toxicity:**

Substance is listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

I

- **TLV (Threshold Limit Value)**

Substance is not listed.

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

Substance is not listed.

- **GHS label elements** The substance is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02

GHS07

GHS08

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/06/2022

Reviewed on 12/06/2022

Trade name: Silver Paint Thinner

(Contd. of page 9)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

4-methylpentan-2-one

· **Hazard statements**

Highly flammable liquid and vapor.

Harmful if inhaled.

Causes serious eye irritation.

Suspected of causing cancer.

May cause respiratory irritation.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** *A Chemical Safety Assessment has not been carried out.*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Contact:**

· **Date of preparation / last revision** 12/06/2022 / -

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 12/06/2022

Reviewed on 12/06/2022

Trade name: Silver Paint Thinner

(Contd. of page 10)

*NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety **Health****TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**BEI: Biological Exposure Limit**Flammable Liquids 2: Flammable liquids – Category 2**Acute Toxicity - Inhalation 4: Acute toxicity – Category 4**Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A**Carcinogenicity 2: Carcinogenicity – Category 2**Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3*

US