

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

1 Identification

- **Product identifier**
- **Trade name:** CURED EPOXY REMOVER - SOLUTION C
- **Article number:** 14942C
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Electron Microscopy Sciences
 1560 Industry Road
 USA-Hatfield, PA 19440
 Tel: 215-412-8400 Fax: 215-412-8450
 email: sgkcck@aol.com
 www.emsdiasum.com
- **Information department:** Product safety department
- **Emergency telephone number:**
 ChemTrec 1-800-424-9300 Contract CCN7661
 1-703-527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Toxicity - Dermal 2

H310 Fatal in contact with skin.



GHS08 Health hazard

Germ Cell Mutagenicity 1B

H340 May cause genetic defects.

Carcinogenicity 1A

H350 May cause cancer.

Specific Target Organ Toxicity - Repeated Exposure 1 H372 Causes damage to the central nervous system and the hematopoietic system through prolonged or repeated exposure.

Aspiration Hazard 1

H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

Trade name: CURED EPOXY REMOVER - SOLUTION C

(Contd. of page 1)

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

benzene

· **Hazard statements**

Highly flammable liquid and vapor.

Fatal in contact with skin.

Causes skin irritation.

Causes serious eye irritation.

May cause genetic defects.

May cause cancer.

Causes damage to the central nervous system and the hematopoietic system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Do not get in eyes, on skin, or on clothing.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Take off immediately all contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

Trade name: CURED EPOXY REMOVER - SOLUTION C

(Contd. of page 2)

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

benzene

>25- ≤50%

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **Special hazards arising from the substance or mixture** No further relevant information available.

- **Advice for firefighters**

- **Protective equipment:** No special measures required.

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

Trade name: CURED EPOXY REMOVER - SOLUTION C

(Contd. of page 3)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:	
benzene	52 ppm
· PAC-2:	
benzene	800 ppm
· PAC-3:	
benzene	4000* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

Trade name: CURED EPOXY REMOVER - SOLUTION C

(Contd. of page 4)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

benzene

PEL	Short-term value: 15* mg/m ³ , 5* ppm Long-term value: 3* mg/m ³ , 1* ppm *table Z-2 for exclusions in 29CFR1910.1028(d)
REL	Short-term value: 1 ppm Long-term value: 0.1 ppm See Pocket Guide App. A
TLV	Short-term value: (2.5) NIC-0.1 ppm Long-term value: (0.5) NIC-0.02 ppm Skin; BEI, A1

· **Ingredients with biological limit values:**

benzene

BEI	25 µg/g creatinine Medium: urine Time: end of shift Parameter: S-Phenylmercapturic acid (background)
	500 µg/g creatinine Medium: urine Time: end of shift Parameter: t,t-Muconic acid (background)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

Trade name: CURED EPOXY REMOVER - SOLUTION C

(Contd. of page 5)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	According to product specification
Odor:	Characteristic
Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	80 °C (176 °F)

· **Flash point:** -11 °C (12.2 °F)

· **Flammability (solid, gaseous):** Highly flammable.

· **Ignition temperature:** 555 °C (1,031 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower:	1.2 Vol %
Upper:	8 Vol %

· **Vapor pressure at 20 °C (68 °F):** 100 hPa (75 mm Hg)

· **Density:** Not determined.

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

Trade name: CURED EPOXY REMOVER - SOLUTION C

(Contd. of page 6)

· **Solvent content:**

Organic solvents:	50.0 %
VOC content:	50.00 %
	500.0 g/l / 4.17 lb/gal

Solids content:	0.0 %
------------------------	-------

· **Other information** *No further relevant information available.*

10 Stability and reactivity

- **Reactivity** *No further relevant information available.*
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **Possibility of hazardous reactions** *No dangerous reactions known.*
- **Conditions to avoid** *No further relevant information available.*
- **Incompatible materials:** *No further relevant information available.*
- **Hazardous decomposition products:** *No dangerous decomposition products known.*

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

benzene

Oral	LD50	4,894 mg/kg (rat)
Dermal	LD50	48 mg/kg (mouse)
Inhalative	LC50/4 h	9,980 mg/l (mouse)

- **Primary irritant effect:**
- **on the skin:** *Irritant to skin and mucous membranes.*
- **on the eye:** *Irritating effect.*
- **Sensitization:** *No sensitizing effects known.*
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
 Irritant
 Carcinogenic.
The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

benzene	I
---------	---

- **NTP (National Toxicology Program)**

benzene	K
---------	---

- **OSHA-Ca (Occupational Safety Health Administration)**

benzene	
---------	--

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

Trade name: CURED EPOXY REMOVER - SOLUTION C

(Contd. of page 7)


12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 3 (Self-assessment): extremely hazardous for water
 Do not allow product to reach ground water, water course or sewage system, even in small quantities.
 Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|--|
| <ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA | <p style="text-align: center;">UN1114</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · ADR · IMDG, IATA | <p style="text-align: center;">Benzene mixture
1114 BENZENE mixture
BENZENE mixture</p> |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT | <div style="text-align: center;">  </div> |
| <ul style="list-style-type: none"> · Class · Label | <p style="text-align: center;">3 Flammable liquids
3</p> |

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

Trade name: CURED EPOXY REMOVER - SOLUTION C

(Contd. of page 8)

· ADR, IMDG, IATA



· Class 3 Flammable liquids
 · Label 3

· Packing group II
 · DOT, ADR, IMDG, IATA II

· Environmental hazards: Not applicable.

· Special precautions for user Warning: Flammable liquids
 · Hazard identification number (Kemler code): 33
 · EMS Number: F-E,S-D
 · Stowage Category B
 · Stowage Code SW2 Clear of living quarters.

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· DOT
 · Quantity limitations On passenger aircraft/rail: 5 L
 On cargo aircraft only: 60 L

· ADR
 · Excepted quantities (EQ) Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml

· IMDG
 · Limited quantities (LQ) 1L
 · Excepted quantities (EQ) Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1114 BENZENE MIXTURE, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture
 · Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

benzene

· TSCA (Toxic Substances Control Act):

	benzene	ACTIVE
14691-87-3	potassium hydroxide periodate	INACTIVE

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

Trade name: CURED EPOXY REMOVER - SOLUTION C

(Contd. of page 9)

· **Hazardous Air Pollutants**

benzene

· **Proposition 65**

· **Chemicals known to cause cancer:**

benzene

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

benzene

· **Chemicals known to cause developmental toxicity:**

benzene

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

benzene

A, K/L

· **TLV (Threshold Limit Value)**

benzene

AI

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

benzene

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02

GHS06

GHS07

GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

benzene

· **Hazard statements**

*Highly flammable liquid and vapor.**Fatal in contact with skin.**Causes skin irritation.**Causes serious eye irritation.**May cause genetic defects.**May cause cancer.**Causes damage to the central nervous system and the hematopoietic system through prolonged or repeated exposure.**May be fatal if swallowed and enters airways.*

· **Precautionary statements**

*Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Keep container tightly closed.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.*

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

Trade name: CURED EPOXY REMOVER - SOLUTION C

(Contd. of page 10)

Do not breathe dust/fume/gas/mist/vapors/spray.

Do not get in eyes, on skin, or on clothing.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Take off immediately all contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Contact:**

· **Date of preparation / last revision** 02/01/2023

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

*OSHA: Occupational Safety **Health***

*TLV: **Threshold Limit Value***

*PEL: **Permissible Exposure Limit***

*REL: **Recommended Exposure Limit***

*BEI: **Biological Exposure Limit***

Flammable Liquids 2: Flammable liquids – Category 2

Acute Toxicity - Dermal 2: Acute toxicity – Category 2

Skin Irritation 2: Skin corrosion/irritation – Category 2

(Contd. on page 12)

Safety Data Sheet
acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

Trade name: CURED EPOXY REMOVER - SOLUTION C

(Contd. of page 11)

*Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A**Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B**Carcinogenicity 1A: Carcinogenicity – Category 1A**Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) – Category 1**Aspiration Hazard 1: Aspiration hazard – Category 1*

US