

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

## 1 Identification

- **Product identifier**
- **Trade name:** CURED EPOXY REMOVER - SOLUTION D
- **Article number:** 14942D
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Electron Microscopy Sciences  
1560 Industry Road  
USA-Hatfield, PA 19440  
Tel: 215-412-8400 Fax: 215-412-8450  
email: sgkcck@aol.com  
www.emsdiasum.com
- **Information department:** Product safety department
- **Emergency telephone number:**  
ChemTrec 1-800-424-9300 Contract CCN7661  
1-703-527-3887

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS01 Exploding bomb

Unstable Explosives

H200 Unstable explosive.



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Toxicity - Inhalation 3

H331 Toxic if inhaled.



GHS07

Acute Toxicity - Oral 4

H302 Harmful if swallowed.

Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS01



GHS02



GHS06



GHS07

(Contd. on page 2)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

**Trade name: CURED EPOXY REMOVER - SOLUTION D**

(Contd. of page 1)

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

*Acetone, Reagent Grade*

*2,4,6-trinitrophenol*

· **Hazard statements**

*Unstable explosive.*

*Highly flammable liquid and vapor.*

*Harmful if swallowed.*

*Toxic if inhaled.*

*Causes serious eye irritation.*

*May cause drowsiness or dizziness.*

· **Precautionary statements**

*Obtain special instructions before use.*

*Do not handle until all safety precautions have been read and understood.*

*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*

*Ground/bond container and receiving equipment.*

*Use explosion-proof electrical/ventilating/lighting/equipment.*

*Use only non-sparking tools.*

*Take precautionary measures against static discharge.*

*Avoid breathing dust/fume/gas/mist/vapors/spray*

*Wash thoroughly after handling.*

*Do not eat, drink or smoke when using this product.*

*Use only outdoors or in a well-ventilated area.*

*Wear protective gloves/protective clothing/eye protection/face protection.*

*Wear personal protective equipment/face protection.*

*If swallowed: Call a poison center/doctor if you feel unwell.*

*Rinse mouth.*

*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*IF INHALED: Remove person to fresh air and keep comfortable for breathing.*

*Call a poison center/doctor.*

*If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.*

*Continue rinsing.*

*Specific treatment (see on this label).*

*If eye irritation persists: Get medical advice/attention.*

*In case of fire: Use CO2, powder or water spray to extinguish.*

*Explosion risk in case of fire.*

*DO NOT fight fire when fire reaches explosives.*

*Evacuate area.*

*Store in accordance with local/regional/national/international regulations.*

*Store in a well-ventilated place. Keep container tightly closed.*

*Store in a well-ventilated place. Keep cool.*

*Store locked up.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



*Health = 2*

*Fire = 3*

*Reactivity = 4*

· **HMIS-ratings (scale 0 - 4)**



*Health = 2*

*Fire = 3*

*Reactivity = 4*

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

**Trade name: CURED EPOXY REMOVER - SOLUTION D**

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

67-64-I	Acetone, Reagent Grade	>50-≤100%
88-89-I	2,4,6-trinitrophenol	>2.5-≤10%

### 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**  
Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Remove persons from danger area.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

**Trade name: CURED EPOXY REMOVER - SOLUTION D**

(Contd. of page 3)

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**· Protective Action Criteria for Chemicals**

· PAC-1:		
67-64-1	Acetone, Reagent Grade	200 ppm
88-89-1	2,4,6-trinitrophenol	0.3 mg/m <sup>3</sup>
· PAC-2:		
67-64-1	Acetone, Reagent Grade	3200* ppm
88-89-1	2,4,6-trinitrophenol	17 mg/m <sup>3</sup>
· PAC-3:		
67-64-1	Acetone, Reagent Grade	5700* ppm
88-89-1	2,4,6-trinitrophenol	100 mg/m <sup>3</sup>

## 7 Handling and storage

**· Handling:**

**· Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

**· Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Prevent impact and friction.

**· Conditions for safe storage, including any incompatibilities**

**· Storage:**

**· Requirements to be met by storerooms and receptacles:** No special requirements.

**· Information about storage in one common storage facility:** Not required.

**· Further information about storage conditions:**

Keep receptacle tightly sealed.

Protect from heat and direct sunlight.

**· Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

**· Additional information about design of technical systems:** No further data; see item 7.

**· Control parameters**

**· Components with limit values that require monitoring at the workplace:**

67-64-1 Acetone, Reagent Grade	
PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: 500 ppm
	Long-term value: 250 ppm
	A4, BEI

(Contd. on page 5)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

**Trade name: CURED EPOXY REMOVER - SOLUTION D**

(Contd. of page 4)

### 88-89-1 2,4,6-trinitrophenol

PEL	Long-term value: 0.1 mg/m <sup>3</sup> Skin
REL	Short-term value: 0.3 mg/m <sup>3</sup> Long-term value: 0.1 mg/m <sup>3</sup> Skin
TLV	Long-term value: 0.1 mg/m <sup>3</sup>

· **Ingredients with biological limit values:**

### 67-64-1 Acetone, Reagent Grade

BEI	25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses



Tightly sealed goggles

US

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

Trade name: CURED EPOXY REMOVER - SOLUTION D

(Contd. of page 5)

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

<b>Form:</b>	Liquid
<b>Color:</b>	According to product specification
<b>Odor:</b>	Characteristic
<b>Odor threshold:</b>	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	56.5 °C (133.7 °F)

· **Flash point:** -20 °C (-4 °F)

· **Flammability (solid, gaseous):** Not flammable.

· **Ignition temperature:** 300 °C (572 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Extreme risk of explosion by shock, friction, fire or other sources of ignition.  
Forms very sensitive explosive metallic compounds.

· **Explosion limits:**

<b>Lower:</b>	2.6 Vol %
<b>Upper:</b>	13 Vol %

· **Vapor pressure at 20 °C (68 °F):** 233 hPa (174.8 mm Hg)

· **Density at 20 °C (68 °F):** 0.8877 g/cm<sup>3</sup> (7.40786 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

**Water:** Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

<b>Dynamic:</b>	Not determined.
<b>Kinematic:</b>	Not determined.

· **Solvent content:**

<b>Organic solvents:</b>	90.0 %
<b>VOC content:</b>	0.00 %
	0.0 g/l / 0.00 lb/gal

**Solids content:** 10.0 %

· **Other information** No further relevant information available.

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

**Trade name: CURED EPOXY REMOVER - SOLUTION D**

(Contd. of page 6)

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**67-64-1 Acetone, Reagent Grade**

Oral	LD50	5,800 mg/kg (rat)
------	------	-------------------

Dermal	LD50	20,000 mg/kg (rabbit)
--------	------	-----------------------

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Irritant

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

**Trade name: CURED EPOXY REMOVER - SOLUTION D**




(Contd. of page 7)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT, ADR, IMDG, IATA</b></li> </ul>   | <p style="text-align: center;">UN1992</p>   |
| <ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG, IATA</b></li> </ul> | <p style="text-align: center;"><i>Flammable liquids, toxic, n.o.s. (Acetone, Trinitrophenol, wetted)</i><br/>1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (ACETONE, TRINITROPHENOL (PICRIC ACID), WETTED)<br/>FLAMMABLE LIQUID, TOXIC, N.O.S. (ACETONE, TRINITROPHENOL (PICRIC ACID), WETTED)</p> |
| <ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>DOT</b></li> </ul>   | <div style="display: flex; align-items: center; justify-content: center;">  </div> <p style="text-align: center;">3 Flammable liquids<br/>3, 6.1</p>   |
| <ul style="list-style-type: none"> <li>· <b>ADR</b></li> </ul>  | <div style="display: flex; align-items: center; justify-content: center;">  </div> <p style="text-align: center;">3 Flammable liquids<br/>3+6.1</p>  |
| <ul style="list-style-type: none"> <li>· <b>IMDG</b></li> </ul>   | <div style="display: flex; align-items: center; justify-content: center;">  </div> <p style="text-align: center;">3 Flammable liquids</p>  |

(Contd. on page 9)

US



# Safety Data Sheet


acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

Trade name: CURED EPOXY REMOVER - SOLUTION D

(Contd. of page 8)

· <b>Label</b>	3/6.1
· <b>IATA</b>	
	
· <b>Class</b>	3 Flammable liquids
· <b>Label</b>	3 (6.1)
· <b>Packing group</b>	
· <b>DOT, ADR, IMDG, IATA</b>	II
· <b>Environmental hazards:</b>	Not applicable.
· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>Hazard identification number (Kemler code):</b>	336
· <b>EMS Number:</b>	F-E,S-D
· <b>Stowage Category</b>	B
· <b>Stowage Code</b>	SW2 Clear of living quarters.
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L
· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 1992 FLAMMABLE LIQUID, TOXIC, N.O.S. (ACETONE, TRINITROPHENOL (PICRIC ACID), WETTED), 3 (6.1), II

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

88-89-1 | 2,4,6-trinitrophenol

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

(Contd. on page 10)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

**Trade name: CURED EPOXY REMOVER - SOLUTION D**

(Contd. of page 9)

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

67-64-1 Acetone, Reagent Grade

I

· **TLV (Threshold Limit Value)**

67-64-1 Acetone, Reagent Grade

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS01

GHS02

GHS06

GHS07

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Acetone, Reagent Grade

2,4,6-trinitrophenol

· **Hazard statements**

Unstable explosive.

Highly flammable liquid and vapor.

Harmful if swallowed.

Toxic if inhaled.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

(Contd. on page 11)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 02/01/2023

Reviewed on 02/01/2023

**Trade name: CURED EPOXY REMOVER - SOLUTION D**

(Contd. of page 10)

Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 Wear personal protective equipment/face protection.  
 If swallowed: Call a poison center/doctor if you feel unwell.  
 Rinse mouth.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 Call a poison center/doctor.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
 Continue rinsing.  
 Specific treatment (see on this label).  
 If eye irritation persists: Get medical advice/attention.  
 In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.  
 Explosion risk in case of fire.  
 DO NOT fight fire when fire reaches explosives.  
 Evacuate area.  
 Store in accordance with local/regional/national/international regulations.  
 Store in a well-ventilated place. Keep container tightly closed.  
 Store in a well-ventilated place. Keep cool.  
 Store locked up.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.  
 • **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Contact:**
- **Date of preparation / last revision** 02/01/2023
- **Abbreviations and acronyms:**  
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety **Health**  
**TLV: Threshold Limit Value**  
**PEL: Permissible Exposure Limit**  
**REL: Recommended Exposure Limit**  
**BEI: Biological Exposure Limit**  
**Unstable Explosives: Explosives – Unstable explosive**  
**Flammable Liquids 2: Flammable liquids – Category 2**  
**Acute Toxicity - Oral 4: Acute toxicity – Category 4**  
**Acute Toxicity - Inhalation 3: Acute toxicity – Category 3**  
**Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A**  
**Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3**