Printing date 01/31/2023 Reviewed on 01/31/2023

1 Identification

· Product identifier

· Trade name: HISTOSOL - XYLENE SUBSTITUTE

· Article number: 23405-01, 23405-04

• CAS Number: 64742-95-6 • EC number: 265-199-0

· Index number: 649-356-00-4

· Application of the substance / the mixture Laboratory chemicals

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Electron Microscopy Sciences 1560 Industry Road USA-Hatfield, PA 19440

Tel: 215-412-8400 Fax: 215-412-8450

email: sgkcck@aol.com www.emsdiasum.com

· Information department: Product safety department

· Emergency telephone number:

ChemTrec 1-800-424-9300 Contract CCN7661

1-703-527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Toxicity - Inhalation 4 H332 Harmful if inhaled.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

Flammable Liquids 4 H227 Combustible liquid.

- · Label elements
- · GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling: Solvent naphtha (petroleum), light arom.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet acc. to OSHA HCS

Reviewed on 01/31/2023 Printing date 01/31/2023

Trade name: HISTOSOL - XYLENE SUBSTITUTE

· Hazard statements

Combustible liquid.

Harmful if inhaled.

May cause respiratory irritation.

May be fatal if swallowed and enters airways.

· Precautionary statements

Keep away from flames and hot surfaces. – No smoking.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Do NOT induce vomiting.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0Fire = 2

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



1 Health = 1

Fire = 2

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description

64742-95-6 Solvent naphtha (petroleum), light arom.

- · Identification number(s)
- EC number: 265-199-0
- · Index number: 649-356-00-4

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)

Printing date 01/31/2023 Reviewed on 01/31/2023

Trade name: HISTOSOL - XYLENE SUBSTITUTE

(Contd. of page 2)

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:

Substance is not listed.

· PAC-2:

Substance is not listed.

· PAC-3:

Substance is not listed.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about protection against explosions and fires: No special measures required.

(Contd. on page 4)

Printing date 01/31/2023 Reviewed on 01/31/2023

Trade name: HISTOSOL - XYLENE SUBSTITUTE

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace: Not required.
- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form:
Color:
Colorless
Odor:
Aromatic
Not determined.

(Contd. on page 5)

Printing date 01/31/2023 Reviewed on 01/31/2023

Trade name: HISTOSOL - XYLENE SUBSTITUTE

	(Contd. of page
pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	<i>-50 °C (-58 °F)</i>
Boiling point/Boiling range:	162 °C (323.6 °F)
· Flash point:	>61 °C (>141.8 °F)
Flammability (solid, gaseous):	Not flammable.
Ignition temperature:	450 °C (842 °F)
Decomposition temperature:	Not determined.
· Auto igniting:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vap
	mixtures are possible.
Explosion limits:	
Lower:	0.7 Vol %
Upper:	7.5 Vol %
Vapor pressure at 20 °C (68 °F):	5 hPa (3.8 mm Hg)
Density at 20 °C (68 °F):	3.5 g/cm³ (29.2075 lbs/gal)
Relative density	Not determined.
· Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water at 20 °C (68 °F):	$0.05~\mathrm{g/l}$
Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Organic solvents:	100.0 %
VOC content:	100.00 %
	3,500.0 g/l / 29.21 lb/gal
Solids content:	0.0 %
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

Printing date 01/31/2023 Reviewed on 01/31/2023

Trade name: HISTOSOL - XYLENE SUBSTITUTE

(Contd. of page 5)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:

64742-95-6 Solvent naphtha (petroleum), light arom.

 Oral
 LD50
 >6,800 mg/kg (rat)

 Dermal
 LD50
 >3,400 mg/kg (rab)

 Inhalative
 LC50/4 h
 >10.2 mg/l (rat)

- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

Substance is not listed.

· NTP (National Toxicology Program)

Substance is not listed.

· OSHA-Ca (Occupational Safety Health Administration)

Substance is not listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

HS

Printing date 01/31/2023 Reviewed on 01/31/2023

Trade name: HISTOSOL - XYLENE SUBSTITUTE

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

4 Transport information	
· UN-Number	
\cdot DOT	Void
· ADR, IMDG, IATA	UN1268
· UN proper shipping name	
$\cdot DOT$	Void
· ADR	1268 PETROLEUM PRODUCTS, N.O.S., ENVIRONMENTALLY HAZARDOUS
· IMDG	PETROLEUM PRODUCTS, N.O.S., MARINE POLLUTANT
· IATA	PETROLEUM PRODUCTS, N.O.S.
· Transport hazard class(es)	
· DOT	
· Class	Void
· ADR, IMDG	
· Class	3 Flammable liquids
· Label	3
· IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group	
$\cdot DOT$	Void
· ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	Symbol (fish and tree)
· Special marking (ADR):	Symbol (fish and tree)
· Special precautions for user · Stowage Category	Warning: Flammable liquids A

Printing date 01/31/2023 Reviewed on 01/31/2023

Trade name: HISTOSOL - XYLENE SUBSTITUTE

	(Contd. of page
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
· ADR	
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
· · ·	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1268 PETROLEUM PRODUCTS, N.O.S. 3, II. ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

Substance is not listed.

Section 313 (Specific toxic chemical listings):

Substance is not listed.

· TSCA (Toxic Substances Control Act):

Substance is not listed.

· Hazardous Air Pollutants

Substance is not listed.

- · Proposition 65
- · Chemicals known to cause cancer:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for females:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for males:

Substance is not listed.

· Chemicals known to cause developmental toxicity:

Substance is not listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

Substance is not listed.

· TLV (Threshold Limit Value)

Substance is not listed.

(Contd. on page 9)

Printing date 01/31/2023 Reviewed on 01/31/2023

Trade name: HISTOSOL - XYLENE SUBSTITUTE

(Contd. of page 8)

· NIOSH-Ca (National Institute for Occupational Safety and Health)

Substance is not listed.

- GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

· Signal word Danger

· Hazard-determining components of labeling:

Solvent naphtha (petroleum), light arom.

· Hazard statements

Combustible liquid.

Harmful if inhaled.

May cause respiratory irritation.

May be fatal if swallowed and enters airways.

· Precautionary statements

Keep away from flames and hot surfaces. – No smoking.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Do NOT induce vomiting.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact:
- · Date of preparation / last revision 01/31/2023
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 10)

(Contd. of page 9)

Safety Data Sheet acc. to OSHA HCS

Printing date 01/31/2023 Reviewed on 01/31/2023

Trade name: HISTOSOL - XYLENE SUBSTITUTE

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 4: Flammable liquids – Category 4

Acute Toxicity - Inhalation 4: Acute toxicity – Category 4

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

Aspiration Hazard 1: Aspiration hazard - Category 1