Printing date 10/20/2022 Reviewed on 10/20/2022

#### 1 Identification

· Product identifier

· Trade name: DUST-OFF PRO

· Article number: 70845-00, 70845-01, 70845-12

• *CAS Number:* 75-37-6

• EC number: 200-866-1

· Application of the substance / the mixture Laboratory chemicals

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Electron Microscopy Sciences 1560 Industry Road USA-Hatfield, PA 19440

Tel: 215-412-8400 Fax: 215-412-8450

email: sgkcck@aol.com www.emsdiasum.com

· Information department: Product safety department

Emergency telephone number:

ChemTrec 1-800-424-9300 Contract CCN7661

1-703-527-3887

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 1

H224 Extremely flammable liquid and vapor.



GHS04 Gas cylinder

Gases under Pressure - Liquefied gas

H280 Contains gas under pressure; may explode if heated.



GHS07

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS04

GHS07

- · Signal word Danger
- · Hazard statements

Contains gas under pressure; may explode if heated.

Extremely flammable liquid and vapor.

(Contd. on page 2)

Printing date 10/20/2022 Reviewed on 10/20/2022

Trade name: DUST-OFF PRO

(Contd. of page 1)

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

*Use only non-sparking tools.* 

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1Fire = 4Reactivity = 1

· HMIS-ratings (scale 0 - 4)



1 Health = 1Fire = 4

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description

75-37-6 1,1-difluoroethane

- · Identification number(s)
- · EC number: 200-866-1

#### 4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. (Contd. on page 3)

Printing date 10/20/2022 Reviewed on 10/20/2022

Trade name: DUST-OFF PRO

(Contd. of page 2)

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

Troccure fiction criteria for chemicus	
· PAC-1:	
	10,000 ppm
· PAC-2:	
	15,000 ppm
· PAC-3:	
	25,000 ppm

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

(Contd. on page 4)

Printing date 10/20/2022 Reviewed on 10/20/2022

Trade name: DUST-OFF PRO

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace: Not required.
- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

#### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Compressed gas

Color: Clear

(Contd. on page 5)

Printing date 10/20/2022 Reviewed on 10/20/2022

Trade name: DUST-OFF PRO

	(Contd. of page
Odor:	Ether-like
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-117 °C (-178.6 °F)
Boiling point/Boiling range:	-26.5 °C (-15.7 °F)
Flash point:	<23 °C (<73.4 °F)
Flammability (solid, gaseous):	Not determined.
Decomposition temperature:	Not determined.
Auto igniting:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vap mixtures are possible.
Explosion limits:	
Lower:	4.9 Vol %
Upper:	20.2 Vol %
Vapor pressure at 20 °C (68 °F):	5,100 hPa (3.800 mm Hg)
Density at 20 °C (68 °F):	0.91 g/cm³ (7.59395 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
Water at 20 °C (68 °F):	5 g/l
Partition coefficient (n-octanol/wate	<b>er):</b> Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
VOC content:	0.00 %
Solids content:	0.0 %
Other information	No further relevant information available.

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

Printing date 10/20/2022 Reviewed on 10/20/2022

Trade name: DUST-OFF PRO

(Contd. of page 5)

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

75-37-6 1,1-difluoroethane

Inhalative LC50/4 h 977 mg/l (mouse)

- Primary irritant effect:
- · on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

Substance is not listed.

· NTP (National Toxicology Program)

Substance is not listed.

· OSHA-Ca (Occupational Safety Health Administration)

Substance is not listed.

#### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

US

Printing date 10/20/2022 Reviewed on 10/20/2022

Trade name: DUST-OFF PRO

(Contd. of page 6)

Transport information	
UN-Number DOT, ADR, IMDG, IATA	UN1030
	0.1110.50
UN proper shipping name DOT	1,1-Difluoroethane
ADR	1030 1,1-DIFLUOROETHANE (REFRIGERANT GAS R 152a)
IMDG, IATA	1,1-DIFLUOROETHANE (REFRIGERANT GAS R 152a)
Transport hazard class(es)	
DOT	
NAME OF	
Class	2.1 Gases
Label	2.1
ADR	
Class	2 2F Gases
Label	2.1
IMDG, IATA	
Class	2.1 Gases
Label	2.1
Packing group DOT, ADR, IMDG, IATA	Void
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Gases
Hazard identification number (Kemler code):	
EMS Number:	F-D,S-U
Stowage Category	B CHA CL CL
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: Forbidden
•	On cargo aircraft only: 150 kg

Printing date 10/20/2022 Reviewed on 10/20/2022

Trade name: DUST-OFF PRO

	(Contd. of page 7
· ADR	Code: E0
· Excepted quantities (EQ)	Not permitted as Excepted Quantity
· IMDG	0
· Limited quantities (LQ)	Code: E0
· Excepted quantities (EQ)	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1030 1,1-DIFLUOROETHANE (REFRIGERANT GAS 1 152A), 2.1

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

Substance is not listed.

Section 313 (Specific toxic chemical listings):

Substance is not listed.

· TSCA (Toxic Substances Control Act):

*ACTIVE* 

- · Hazardous Air Pollutants
- Substance is not listed.
- · Proposition 65
- · Chemicals known to cause cancer:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for females:

Substance is not listed.

· Chemicals known to cause reproductive toxicity for males:

Substance is not listed.

· Chemicals known to cause developmental toxicity:

Substance is not listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

Substance is not listed.

· TLV (Threshold Limit Value)

Substance is not listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

Substance is not listed.

· GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 9)

(Contd. of page 8)

### Safety Data Sheet acc. to OSHA HCS

Printing date 10/20/2022 Reviewed on 10/20/2022

Trade name: DUST-OFF PRO

· Hazard pictograms







GHS02

2 GHS04

- · Signal word Danger
- · Hazard statements

Contains gas under pressure; may explode if heated.

Extremely flammable liquid and vapor.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Contact:
- Date of preparation / last revision 10/20/2022 / -
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit

(Contd. on page 10)

Printing date 10/20/2022 Reviewed on 10/20/2022

Trade name: DUST-OFF PRO

(Contd. of page 9)

 $REL: Recommended\ Exposure\ Limit$ 

Gases under Pressure - Liquefied gas: Gases under pressure - Liquefied gas
Flammable Liquids 1: Flammable liquids - Category 1
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3